

TIRES

The ATC Super Red 250 is equipped with OHTSU 25x12.00-9 low pressure tubeless tires to provide a comfortable ride. Although the tires are designed specifically for vigorous off-road use, they are not immune to punctures. Always select your riding area with care.

CAUTION:

- * *Driving on paved surfaces will cause excessive tire wear.*

For normal use, the tires should be inflated to a recommended pressure of 2.2 psi (15 kPa, 0.15 kg/cm²). A manually operated tire pump should be used rather than the high pressure systems found in service stations. This will minimize the possibility of tire damage from overinflation.

NOTE:

- * Tire pressure should be checked when the tires are “cold,” before you ride.

If no air pressure gauge is available to accurately measure air pressure, this value can be estimated by measuring the circumference of the tires with a measuring tape. When inflated to the recommended pressures, the maximum tire circumference measured over the tread ribs will be approximately 1,915 mm (79.3

in.). The relationship between tire pressure and actual circumference varies slightly with factors of wear and stretching that occur through use.

Recommended Pressure:

2.2 psi (15 kPa, 0.15 kg/cm²)

Standard Tire Circumference: 1,915 mm (79.3 in.)

WARNING

- * *The ATC is not designed to be ridden on paved surfaces.*

Handling and control will be severely affected.

