

MAINTENANCE SCHEDULE

Perform the Pre-ride Inspection (page 86) at each scheduled maintenance period.

I: INSPECT AND CLEAN, ADJUST, LUBRICATE OR REPLACE IF NECESSARY.

C: CLEAN R: REPLACE A: ADJUST L: LUBRICATE

ITEM		FREQUENCY	WHICHEVER COMES FIRST ↓ EVERY	ODOMETER READING [NOTE (3)]						REFER TO
				600 mi (1,000 km)	4,000 mi (6,400 km)	8,000 mi (12,800 km)	12,000 mi (19,200 km)	16,000 mi (25,600 km)	20,000 mi (32,000 km)	
*	FUEL LINES			I	I	I	I	I		
*	FUEL STRAINER			C	C	C	C	C		
*	THROTTLE OPERATION			I	I	I	I	I		
*	CARBURETOR-CHOKE			I	I	I	I	I		
	AIR CLEANER	NOTE (1)		C	R	C	R	C	Page 124	
	CRANKCASE BREATHER	NOTE (2)		C	C	C	C	C	Page 168	
	SPARK PLUGS			R	R	R	R	R	Page 114	
*	VALVE CLEARANCE			I	I	I	I	I		
	ENGINE OIL	YEAR		R	R	R	R	R	Pages 106	
	ENGINE OIL FILTER	YEAR		R	R	R	R	R	Page 112	
*	CAM CHAIN TENSION			A	A	A	A	A		
*	CARBURETOR- SYNCHRONIZATION			I	I	I	I	I		
*	CARBURETOR- IDLE SPEED			I	I	I	I	I	Page 128	