

**SPECIFICATIONS**

GENERAL	ITEM	SPECIFICATIONS
DIMENSIONS	Overall length Overall width Overall height Wheelbase Seat height Footpeg height Ground clearance Dry weight Curb weight	1,910 mm (75.2 in) 652 mm (25.7 in) 1,065 mm (41.9 in) 1,286 mm (50.6 in) 776 mm (30.6 in) 312 mm (12.3 in) 172 mm (6.8 in) 115 kg (253.53 lbs) 123 kg (271.17 lbs)
FRAME	Frame type Front suspension Front axle travel Rear suspension Rear axle travel Rear damper Front tire size Rear tire size Tire brand Front brake Rear brake Caster angle Trail length Fuel tank capacity	Diamond type Telescopic fork 190 mm (4.29 in) Swingarm 120 mm (4.72 in) Single effected tube type 80/90-17M/C 44P 100/80-17M/C 52P Front/Rear: IRC Hydraulic disc brake Hydraulic disc brake 25° 88 mm (3.46 in) 10.0 liter (2.64 US gal, 2.2 Imp gal)
ENGINE	Bore and stroke Displacement Compression ratio Valve train Intake valve Exhaust valve Lubrication system Oil pump type Cooling system Air filtration Crankshaft type Engine dry weight Cylinder arrangement	63.5 x 47.2 mm (2.50 x 1.86 in) 149.4 cm <sup>3</sup> (9.1 cu-in) 11.0: 1 Multi link chain drive and DOHC 5° BTDC 35° ABDC 30° BBDC 0° ATDC Forced pressure and wet sump Trochoid Liquid cooled Paper filter Assembled type 26.1 kg (57.55 lbs) Single cylinder inclined 40° from vertical

