

## MAINTENANCE

### MAINTENANCE SCHEDULE

Perform the Pre-ride Inspection (Page68) at each scheduled maintenance period.

I: Inspect and Clean, Adjust, Lubricate or Replace, if necessary.

C: Clean. R: Replace. A: Adjust. L: Lubricate

ITEM		FREQUENCY	WHICHEVER COMES FIRST → ↓	ODOMETER (NOTE 3)				Page
				1,000km (600mi)	6,000km (3,600mi)	12,000km (7,200mi)	18,000km (10,800mi)	
		EVERY						
*	FUEL LINES			I	I	I	—	
*	FUEL STRAINER		C	C	C	C	—	
*	THROTTLE OPERATION		I	I	I	I	138	
*	CARBURETOR CHOKE			I	I	I	—	
	AIR CLEANER	NOTE 1		C	C	C	134	
	SPARK PLUG			I	R	I	116	
*	VALVE CLEARANCE		I	I	I	I	120	
	ENGINE OIL	YEAR R	R	REPLACE EVERY 3,200km (2,000mi)			106	
	ENGINE OIL FILTER SCREEN	YEAR C		C	C	C	108	
*	ENGINE OIL FILTER ROTOR				C		110	
*	CAM CHAIN TENSION		A	A	A	A	132	
*	CARBURETOR IDLE SPEED		I	I	I	I	140	