

CX500TURBO

SPECIFICATIONS

ESPECIFICACIONES

DIMENSIONS Overall length Overall width Overall height Wheelbase	DIMENSIONES Longitud total Anechura total Altura total Batalla	2,260 mm (89.0 in) 720 mm (28.3 in) 1,345 mm (53.0 in) 1,495 mm (58.9 in)
WEIGHT Dry weight	PESOS Peso seco	239 kg (527 lbs)
CAPACITIES Passenger capacity Engine oil (After draining) Final drive gear oil Fuel tank Cooling system capacity	CAPACIDADES Número de asientos Aceite de motor (Reemplace) Aceite del engranaje de mando final Depósito de combustible Capacidad del sistema de enfriamiento	Operator and one passenger Uno para motociclista y otro para un acompañante 3.0 liter (3.2 U.S. qt., 2.6 Imp. qt.) 0.17 liter (0.18 U.S. qt., 0.15 Imp. qt.) 20 liter (5.3 U.S. gal., 4.5 Imp. gal.) 2.1 liter (2.2 U.S. qt., 1.7 Imp. qt.)
ENGINE Bore and stroke Compression ratio Displacement Spark plug gap Valve tappet clearance Intake Exhaust	MOTOR Alesaje y carrera Relación de compresión Cilindrada Claro de la bujía de encendido Luz de válvulas Admisión Descarga	78 x 52 mm (3.07 x 2.05 in) 7.2 : 1 496 cm ³ (30.3 cu-in) 0.8-0.9 mm (0.03-0.04 in) 0.10 mm (0.004 in) 0.12 mm (0.005 in)
CHASSIS AND SUSPENSION Caster Trail Tire size, front Tire size, rear	CHASSIS Y SUSPENSION Inclinación del puente delantero Trazo Tamaño de la llante, delantera Tamaño de la llanta, trasera	63° 110 mm (4.3 in) 3.50V18 (4PR) 120/90V17
POWER TRANSMISSION Primary reduction Gear ratio, 1st. 2nd. 3rd. 4th. 5th. Final reduction	TRANSMISION DE FUERZA Reducción primaria Relación de engranajes, 1 ^a 2 ^a 3 ^a 4 ^a 5 ^a Reducción final	2.055 (74/36) 2.500 (40/16) 1.714 (36/21) 1.280 (32/25) 1.035 (29/28) 0.838 (26/31) 0.324 (11/34)
ELECTRICAL Battery Generator	SISTEMA ELECTRICO Batería Generador	12V - 14AH A.C. generator Generador de c.a.