

Specifications

Recommended drive chain lubricant	Drive chain lubricant designed specifically for O-ring chains	
Drive chain slack	25 to 35 mm (1.0 to 1.4 in)	
	DID 520V0 or RK 520MKO	
Standard drive chain		NC700S/SA
	No. of links	114
		NC700SD
		112
	Engine sprocket	16T
Standard sprocket sizes		NC700S/SA
	Rear wheel sprocket	43T
		NC700SD
		39T

■ Bulbs

Headlight	12V-60/55W	
Brake/Tail light	12V-21/5W	
Front turn signal lights	12V-21W × 2	
Rear turn signal lights	12V-21W × 2	
Position light	12V-5W	

■ Fuses

Main fuse	30A	
Other fuses	NC700S	15A, 7.5A
	NC700SA/SD	30A, 15A, 7.5A

■ Torque Specifications

Maintenance lid screws	3 N·m (0.3 kgf·m, 2.2 lbf·ft)
Engine oil drain bolt	30 N·m (3.1 kgf·m, 22 lbf·ft)
Oil filter	26 N·m (2.7 kgf·m, 19 lbf·ft)
Front wheel axle shaft	74 N·m (7.5 kgf·m, 55 lbf·ft)
Front wheel brake caliper mounting bolts	30 N·m (3.1 kgf·m, 22 lbf·ft)
Front wheel axle pinch bolt	22 N·m (2.2 kgf·m, 16 lbf·ft)
Rear wheel axle nut	98 N·m (10.0 kgf·m, 72 lbf·ft)
NC700SD only	
Parking brake caliper mounting bolts	31 N·m (3.2 kgf·m, 23 lbf·ft)
Drive chain adjusting lock nuts	21 N·m (2.1 kgf·m, 15 lbf·ft)
Brake/tail light assembly screw C	6 N·m (0.6 kgf·m, 4.4 lbf·ft)