

■ Service Data

Tire size	Front	120/90-10 57J
	Rear	130/90-10 61J
Tire type	Bias-ply, tubeless	
Recommended Tires	Front	KENDA K761
	Rear	KENDA K761
Tire air pressure	Front	25 psi (175 kPa, 1.75 kgf/cm ²)
	Rear	25 psi (175 kPa, 1.75 kgf/cm ²)
Minimum tread depth	Front	0.03 in (0.8 mm)
	Rear	0.03 in (0.8 mm)
Spark plug	(standard)	CR8EH-9 (NGK)
	(cold climate)	CR7EH-9 (NGK)
	(high speed riding)	CR9EH-9 (NGK)
Spark plug gap	0.031 to 0.035 in (0.80 to 0.90 mm)	
Idle speed	2,000 ± 100 rpm	
Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	

Engine oil capacity	After draining	0.6 US qt (0.6 liters)
	After draining & engine oil strainer screen cleaning	0.7 US qt (0.7 liters)
	After disassembly	0.7 US qt (0.7 liters)
Cooling system capacity	0.51 US qt (0.48 liters)	
Recommended coolant	Pro Honda HP Coolant	

■ Bulbs

Headlights	12V-35/35W x 2
Brake/Taillight	12V-27/8W
Front turn signal lights	12V-23W x 2
Rear turn signal lights	12V-23W x 2

■ Fuses

Main fuse	20A
Other fuses	10A

■ Torque Specifications

Engine oil drain bolt	18 lbf·ft (24 N·m, 2.4 kgf·m)
Oil plug	15 lbf·ft (20 N·m, 2.0 kgf·m)