

SPECIFICATIONS

DIMENSIONS

Overall length	2,285 mm (89.9 in)
Overall width	835 mm (32.9 in)
Overall height	1,395 mm (54.9 in)
Wheelbase	1,555 mm (61.2 in)
Ground clearance	145 mm (5.7 in)

WEIGHT

Dry weight	283 kg (624 lbs)
Equipped with the ABS and TCS	293 kg (646 lbs)

CAPACITIES

Engine oil:	
After draining	3.6 ℓ (3.8 US qt, 3.2 Imp qt)
After oil filter change	3.7ℓ (3.9 US qt, 3.3 Imp qt)
After disassembly	4.3 ℓ (4.5 US qt, 3.8 Imp qt)
Final drive gear oil	150 cc (5.1 oz) After draining
Fuel tank	28 ℓ (7.4 US gal, 6.1 Imp gal)
Cooling system capacity	3.0 ℓ (3.2 US qt, 2.7 Imp qt)
Passenger capacity	Operator and one passenger
Maximum weight capacity	205 kg (452 lb)
Equipped with the ABS and TCS	195 kg (430 lb)

ENGINE

Bore and stroke	73 × 64.8 mm (2.87 × 2.55 in)
Compression ratio	10 : 1
Displacement	1,084 cc (66.1 cu.in)
Spark plug	
Standard	U24FER9 (NIPPONDENSO), CR8EH9 (NGK)
For extended high speed riding	U27FER9 (NIPPONDENSO), CR9EH9 (NGK)
Spark plug gap	0.8—0.9 mm (0.031—0.036 in)
Idle speed	1,000 ± 100 rpm 1,200 ± 50 rpm (SW type)