

# Specifications

<b>Chassis &amp; Suspension</b>	
caster	2.0°
trail	0.1 in (3 mm)
tire size, front	AT25 × 8-12 ★★ DUNLOP KT181
tire size, rear	AT25 × 10-12 ★★ DUNLOP KT185
<b>TRX500FE</b>	
tire pressure, front & rear (cold)	3.6 psi (25 kPa , 0.25 kgf/cm <sup>2</sup> )
maximum tire pressure, front & rear (cold)	4.0 psi (28 kPa , 0.28 kgf/cm <sup>2</sup> )
minimum tire pressure, front & rear (cold)	3.2 psi (22 kPa , 0.22 kgf/cm <sup>2</sup> )
<b>TRX500FPE</b>	
tire pressure, front & rear (cold)	Front: 4.4 psi (30 kPa , 0.30 kgf/cm <sup>2</sup> ) Rear: 3.6 psi (25 kPa , 0.25 kgf/cm <sup>2</sup> )
maximum tire pressure, front & rear (cold)	Front: 5.0 psi (34 kPa , 0.34 kgf/cm <sup>2</sup> ) Rear: 4.0 psi (28 kPa , 0.28 kgf/cm <sup>2</sup> )
minimum tire pressure, front & rear (cold)	Front: 3.8 psi (26 kPa , 0.26 kgf/cm <sup>2</sup> ) Rear: 3.2 psi (22 kPa , 0.22 kgf/cm <sup>2</sup> )