

MAINTENANCE SCHEDULE

Perform the Pre-ride Inspection at each scheduled maintenance period.

I : INSPECT AND CLEAN, ADJUST, LUBRICATE OR REPLACE IF NECESSARY

C : CLEAN R : REPLACE A : ADJUST L : LUBRICATE

ITEM	FREQUENCY	WHICHEVER COMES FIRST ↓	ODOMETER READING (NOTE (3))						PAGE
			1,000 km (600 mi)	6,400 km (4,000 mi)	12,800 km (8,000 mi)	19,200 km (12,000 mi)	25,600 km (16,000 mi)	32,000 km (20,000 mi)	
		EVERY							
* FUEL LINES					I		I	I	
* FUEL STRAINER						C	C	C	C
* FUEL FILTER									R
* THROTTLE OPERATION			I		I		I		I
* CARBURETOR-CHOKE					I		I		I
* AIR CLEANER		NOTE (1)			R		R		R
CRANKCASE BREATHER		NOTE (2)			C	C	C	C	C
SPARK PLUGS					I	R	I	R	I
* VALVE CLEARANCE			I		I		I		I
ENGINE OIL		YEAR	R		R		R		R
ENGINE OIL FILTER		YEAR	R		R		R		R
* CARBURETOR- SYNCHRONIZATION			I		I		I		I
* CARBURETOR- IDLE SPEED			I	I	I	I	I	I	I
RADIATOR COOLANT					I		I		*R
* RADIATOR CORE					I		I		I
* COOLING SYSTEM HOSES & CONNECTIONS			I		I		I		I