


Safety Labels



Motorcycle Safety

8

⟨For USA⟩

TIR	E INFOR	MATION
COLD TIRE PRESSU	CUT CARACITY FRONT 2	50kPa 2.50kgf/cm² 36psi. 90kPa 2.90kgf/cm² 42psi.
UP TO 90kg (2001	bs.) LOAD REAR 2	50kPa 2.50kgf/cm² 36psi. 90kPa 2.90kgf/cm² 42psi. { 366 lbs. }
	FRONT 120/70ZR17M/C (58	W) REAR 190/50ZR17M/C (73W)
DUNLOP D2	RONT REAR 108FN B208N NONTRACING MEZSH RACING	Read Owner's Manual
MIN.RECOMMEND TIR		THIS MOTORCYCLE IS EQUIPPED WITH TUBELESS TIRES.

⟨For CANADA⟩

TIRE	INFORMATION
COLD TIME PRESSURES : [UP TO MAXIMUM WEIGHT CAPA	CITY] FRONT 250kPa 2.50kgf/cm² 36psi REAR 290kPa 2.90kgf/cm² 42psi
(UP TO 90kg (2001bs.) LO Maximum Weight Capacity	ncan 250kra 2.50kgi/cm 42psi
TIRE SIZE : FRONT 1	120/70ZR17M/C (58W) REAR 190/50ZR17M/C (73W
TIRE BRAND FRONT DUNLOP D208FN METZELER NEZ3H FRONT RACING	REAR D204N REFINERACING Read Owner's Manual
MIN.RECOMMEND TIRE CENTI	ER TREAD DEPTH THIS MOTORCYCLE IS EQUIPPED WITH TUBELESS TIRES.

