

# Specifications

## Main Components

Type	KF12
Overall length	1,915 mm (75.4 in)
Overall width	740 mm (29.1 in)
Overall height	1,090 mm (42.9 in)
Wheelbase	1,315 mm (51.8 in)
Minimum ground clearance	130 mm (5.1 in)
Caster angle	27° 00'
Trail	86 mm (3.4 in)
Curb weight	129 kg (284 lb)
Maximum weight capacity*1	180 kg (397 lb)
Maximum luggage weight*2	13 kg (29 lb)
	Centre compartment Glove box
Passenger capacity	Rider and 1 passenger
Minimum turning radius	1.98 m (6.50 ft)

\*1 Including rider, passenger, all luggage, and accessories

\*2 Includes the weight of the luggage and added accessories.

Displacement	153 cm <sup>3</sup> (9.3 cu-in)
Bore x stroke	58.0 x 57.9 mm (2.28 x 2.28 in)
Compression ratio	10.6:1
Fuel	Unleaded petrol Recommended: 91 RON or higher
Tank capacity	5.9 litres (1.56 US gal, 1.30 Imp gal)
Battery	YTZ7S 12 V-6 Ah (10 HR) / 6.3 Ah (20 HR)
Primary reduction	V-Matic (2.45:1-0.81:1)
Final reduction	10.552