MAINTENANCE SCHEDULE

- Perform the Pre-ride inspection in the Owner's Manual at each scheduled maintenance period.
- I: Inspect and Clean, Adjust, Lubricate or Replace if necessary. C: Clean. R: Replace. A: Adjust. L: Lubricate.
- The following items require some mechanical knowledge. Certain items (particularly those marked * and **) may require more technical information and tools. Consult a dealer.



Refer to "Basic" Service Manual for each maintenance instruction except the instructions described in this
manual.

ITEMS		FREQUENCY (NOTE 1)						DEOLUAD.	DEEED
	NOTE	X1,000 km	1	4	8	12	ANNUAL CHECK	REGULAR REPLACE	
		X1,000 mi	0.6	2.5	5	7.5			
* FUEL LINE				I	ı	ı			
* THROTTLE OPERATION				ı	ı	ı	I		
* AIR CLEANER	NOTE2	Every 16000 km (10000 mi) R							→ 2-7
CRANKCASE BREATHER	NOTE3			С	С	С	С		
SPARK PLUG				ı	R	ı			→ 4-22
* VALVE CLEARANCE			ı	I	ı	ı			→ 2-15
ENGINE OIL			R	R	R	R	R		→ 2-14
** ENGINE OIL STRAINER						С			→ 2-14
SCREEN									72-14
** ENGINE OIL						С			→ 2-22
CENTRIFUGAL FILTER						Ŭ			7
* ENGINE IDLE SPEED			ı	I	ı	ı	l		
* EVAPORATIVE EMISSION						ı			
CONTROL SYSTEM					L				
DRIVE CHAIN		Every 1000 km (600 mi) I, L							
BRAKE FLUID	NOTE4			l l	ı	ı		2 years	
BRAKE PADS WEAR				I	ı	ı	l		
BRAKE SYSTEM			ı	ı	ı	ı	l		
BRAKE LIGHT SWITCH				I	ı	ı	l		
HEADLIGHT AIM				I	ı	ı	l		→ 4-30
CLUTCH SYSTEM			ı	I	ı	ı	I		
SIDESTAND				I	ı	ı	I		
* SUSPENSION					I	I			
* NUTS, BOLTS,			ı		1		ı		
FASTENERS							· ·		
** WHEELS/TIRES					I	I			
** STEERING HEAD			1			1			
BEARINGS			_ '			<u>'</u>	'		

- * Should be serviced by a dealer, unless the owner has proper tools and service data and is mechanically qualified.
- ** In the interest of safety, we recommend these items be serviced only by a dealer.
- Honda recommends that a dealer should road test the vehicle after each periodic maintenance is carried out.

NOTES:

- 1. At higher odometer readings, repeat at the frequency interval established here.
- 2. Service more frequently when riding in unusually wet or dusty areas.
- 3. Service more frequently when riding in rain or at full throttle.
- 4. Replacement requires mechanical skill.