

LIGHTS/METERS/SWITCHES

ITEM		SPECIFICATIONS	
Bulbs	Headlight	High beam	12V – 55W
		Low beam	12V – 55W
	Position light (Except U type)		12V – 5W
	Brake/tail light		12V – 21/5W × 2
	Front turn signal light		12V – 21W × 2
	Rear turn signal light		12V – 21W × 2
	Instrument light		12V – 1.7W × 4
	Turn signal indicator		12V – 3W × 2
	High beam indicator		12V – 3W
	Neutral indicator		12V – 3W
	Oil pressure indicator		12V – 3W
	PGM-FI warning indicator		12V – 3W
	Immobilizer indicator		LED
Fuse	Main fuse		30A
	PGM-FI fuse		30A
	Sub fuse		20A × 1, 10A × 5
Tachometer peak voltage		10.5 V minimum	
Thermo sensor resistance	80 °C	47.5 – 56.8 kΩ	
	120 °C	14.9 – 17.3 kΩ	
Fuel level sensor resistance	Full	4 – 10 Ω	
	Empty	81 – 91 Ω	
Fan motor switch	Start to close (ON)	98 – 102 °C (208 – 216 °F)	
	Stop to open	93 – 97 °C (199 – 207 °F)	

TORQUE VALUES

Side stand mounting bolt	10 N·m (1.0 kgf·m , 7 lbf·ft)	
Side stand lock nut	29 N·m (3.0 kgf·m , 22 lbf·ft)	
Side stand switch mounting bolt	10 N·m (1.0 kgf·m , 7 lbf·ft)	ALOC bolt
Side stand bracket bolt	54 N·m (5.5 kgf·m , 40 lbf·ft)	ALOC bolt
Ignition switch mounting bolt	25 N·m (2.5 kgf·m , 18 lbf·ft)	
Coolant temperature sensor	10 N·m (1.0 kgf·m , 7 lbf·ft)	Apply sealant to the threads
Neutral switch	12 N·m (1.2 kgf·m , 9 lbf·ft)	
Oil pressure switch	12 N·m (1.2 kgf·m , 9 lbf·ft)	Apply sealant to the threads
Oil pressure switch terminal screw	2 N·m (0.2 kgf·m , 1.4 lbf·ft)	